SUBMERSIBLE PRESSURE TRANSMITTER ECL

- Suitable also for thick and viscous media
- Different materials for optimum media compatibility
- Configurable measuring ranges
- Optional: Enhanced lightning protection





Submersible Pressure Transmitter ECL 8439

Swiss based Trafag is a leading international supplier of high quality sensors and monitoring instruments for measurement of pressure and temperature. The new Submersible Pressure Transmitter ECL is based on Trafag's own thick-film-on-ceramic technology. The optionally configurable pressure ranges can be adapted individually via interface tool and Smartphone App.



Applications


- Shipbuilding
- Process technology
- Water treatment (wastewater, grey-water, drinking water)
- Seawater


Features

- Suitable also for thick and viscous media
- Different materials for optimum media compatibility
- Configurable measuring ranges
- Optional: Enhanced lightning protection





Technical Data			
Measuring principle	Thick-film-on-ceramic	Accuracy @ 25°C typ.	\pm 0.3 % FS typ. Range 0 0.1 to 0 0.2 bar: \pm 0.5 % FS typ.
Measuring range	0 0.1 to 0 6.0 bar 0 1.5 to 0 100 psi	Media temperature	max25°C +70°C
Output signal	4 20 mA	Ambient temperature	max25°C +70°C
NLH @ 25°C (BSL) typ.	± 0.2 % FS typ. Range 0 0.1 to 0 0.2 bar: ± 0.3 % FS typ.	Approval / conformity	DNV-GL EU RO Mutual Recognition Type Approval Certificate











F = max. 10 kg (100 N)

Serto adapter SO 50021-12 for stainless steel tubes with: outer diameter 12 mm inner diameter 8 mm



